

इंटरनेट

मानक

### Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan


“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”


IS 5455 (1969): cast-iron steps for manholes [CED 3: Sanitary Appliances and Water Fittings]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



**IS : 5455 - 1969**

***Indian Standard***  
**SPECIFICATION FOR**  
**CAST IRON STEPS FOR MANHOLES**  
( Fourth Reprint JUNE 1990 )

UDC 628.253.2

© Copyright 1970

**BUREAU OF INDIAN STANDARDS**  
**MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG**  
**NEW DELHI 110002**

# Indian Standard

## SPECIFICATION FOR CAST IRON STEPS FOR MANHOLES

---

Water Supply and Sanitation Sectional Committee, BDC 24

### Chairman

**SHRI N. V. MODAK**

### Representing

Institution of Engineers ( India ), Calcutta

### Members

**SHRI D. APPUKUTTAN NAIR**

Public Health Engineering Department, Government of Kerala

**PROF S. J. ARCEIVALA**

Central Public Health Engineering Research Institute ( CSIR ), Nagpur

**SHRI J. M. DAVE ( Alternate )**

**SHRI H. R. BADYAL**

The Indian Iron & Steel Co Ltd, Calcutta

**SHRI K. R. PANDALAI ( Alternate )**

**SHRI J. R. BHALLA**

The Indian Institute of Architects, Bombay

**DR B. V. BHOOTA**

Dorr-Oliver ( India ) Ltd, Bombay

**SHRI M. L. SHAH ( Alternate )**

**CHIEF ENGINEER**

Local Self Government Engineering Department, Lucknow

**SUPERINTENDING ENGINEER ( Alternate )**

**CHIEF ENGINEER ( WATER )**

Delhi Municipal Corporation

**DRAINAGE ENGINEER ( Alternate )**

**SHRI V. D. DESAI**

Bombay Municipal Corporation

**SHRI L. G. DHAYAGUDE ( Alternate )**

**SHRI T. DURAIRAJ**

Ministry of Health, Family Planning, Works, Housing and Urban Development

**SHRI S. RADHAKRISHNAN ( Alternate )**

**SHRI K. C. JERATH**

Engineer-in-Chief's Branch, Army Headquarters

**SHRI P. SESHADRI ( Alternate )**

**SHRI M. A. KARIM**

Corporation of Madras

**SHRI M. Y. MADAN**

The Hindustan Construction Co Ltd, Bombay

**SHRI B. S. MAHANTANNAVAR**

Public Works Department, Government of Mysore

**SHRI N. MAJUMDER**

All India Institute of Hygiene & Public Health, Calcutta

**SHRI S. K. MAJUMDER**

Public Health Engineering Department, Government of West Bengal

**SHRI B. K. MALHAN**

John Tinson & Co Private Ltd, New Delhi

**SHRI M. MIKHAHAN**

Public Health Engineering Department, Government of Tamil Nadu

**SHRI K. S. NARAYANAN**

Central Public Works Department

**SHRI S. V. PATWARDHAN**

University of Roorkee, Roorkee

**PUBLIC HEALTH ENGINEER**

Public Health Department, Government of Madhya Pradesh

( Continued on page 6 )

**BUREAU OF INDIAN STANDARDS**

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

# *Indian Standard*

## SPECIFICATION FOR CAST IRON STEPS FOR MANHOLES

### 0. FOREWORD

**0.1** This Indian Standard was adopted by the Indian Standards Institution on 2 December 1969, after the draft finalized by the Water Supply and Sanitation Sectional Committee had been approved by the Civil Engineering Division Council.

**0.2** Cast iron steps (rungs) are commonly fitted in the walls of manholes for providing access to the sewers from the manhole openings. They should be of proper quality and suitably designed so as to ensure safety of persons using them and there have been cases of accidents due to unsatisfactory designs. This standard has been prepared to give guidance for the proper manufacture and construction of cast iron steps and it is hoped it will be found useful by the Public Health Engineering Departments, Municipal Corporations and others.

**0.3** This standard contains clauses 3.3.1 and 5.1 which call for agreement between the purchaser and the supplier.

**0.4** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

---

### 1. SCOPE

**1.1** This standard lays down the requirements for cast iron steps for manholes.

### 2. MATERIAL

**2.1** The steps shall be of suitable quality grey cast iron not inferior to grade 15 of IS: 210-1962†.

\*Rules for rounding off numerical values (*revised*).

†Specification for grey iron castings (*revised*) (Since revised).


### 3. MANUFACTURE

**3.1** The steps shall be clean, well-cast and they shall be free from air and sand holes, cold shuts and warpings which are likely to impair the utility of the castings.

**3.2** The portion of the step which projects from the wall of the manhole shall have a raised chequered design to provide an adequate non-slip grip. Any ribs, chequering, lettering or other projection for this purpose shall be raised above the general plane of the top surface of the step and shall be placed particularly along the edges of the tread. It is considered that in this position the most protection is given against slip.


**NOTE** — The chequered pattern shown in Fig. 1A and Fig. 1B shall not be regarded as of a particular design.

**3.3** The dimensions of steps shall be as shown in pattern 1, or pattern 2 of Fig. 1A and Fig. 1B. A tolerance of  $\pm 2$  mm shall be permissible on the dimensions.



All dimensions in millimetres.

FIG. 1A CAST IRON STEPS FOR MANHOLE (PATTERN 1)



All dimensions in millimetres.

FIG. 1B CAST IRON STEPS FOR MANHOLE ( PATTERN 2 )

**3.3.1** The steps may be manufactured in other dimensions where so agreed to between the manufacturer and the purchaser.

**3.4 Minimum Weights** — The minimum weights of cast iron steps shall be as under:

Pattern 1 4.5 kg

Pattern 2 5.3 kg

#### 4. COATING

**4.1** The cast iron steps shall be coated with a material having tar base or with a black bituminous composition or cashew-nut shell liquid. The coating shall be smooth and tenacious. It shall not flow when exposed to a temperature of 63°C and shall not be brittle as to chip of at temperature of 0°C.



## 5. TESTS

**5.1** One sample of step out of 50 samples may be subjected to a load test as given in Appendix A where so agreed to between the manufacturer and the purchaser. If this test is required the arrangement ( which shall include the cost of the test ) shall be as agreed to between the manufacturer and the purchaser.

## 6. MARKING

**6.1** Each cast iron step shall have the following information:

- a) Manufacturer's name or trade-mark, and
- b) Pattern ( *see* 3.3 ).

**6.1.1** Each cast iron step may also be marked with the ISI Certification Mark.

**NOTE** — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution ( Certification Marks ) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

## A P P E N D I X A

( *Clause 5.1* )

### LOAD TEST

#### A-1. DETAILS

**A-1.1** The test specimen shall be clamped in a horizontal plane so as to leave only the tread portion projected as a canti-lever in the manner shown in Fig. 2. It is important that the position of the centre nib shall be accurately placed so as to perform its proper function in the canti lever position.

**A-1.2** A load of 225 kg shall be applied vertically at a point at the centre of the front tread ( *see* Fig. 3 ). This load shall be applied gradually and without stop. The test specimen shall withstand the load for a period of one minute without signs of cracking or other injury or permanent setting.




FIG. 2 INDICATION OF MANNER OF SUPPORTING CAST IRON STEP FOR PROOF LOAD TEST




FIG. 3 INDICATION OF LOAD APPLICATION FOR PROOF LOAD TEST

( Continued from page 1 )

*Members*

SHRI P. B. RAO

SHRI L. R. SEHGAL

SHRI D. R. SINGAL

TOWN ENGINEER, CHITTARANJAN  
LOCOMOTIVE WORKS

SHRI R. NAGARAJAN,  
Director ( Civ Engg )

*Representing*

Central Building Research Institute ( CSIR )  
Roorkee

S. D. Marker & Co Private Ltd, New Delhi

Public Works Department, Government of Punjab  
Ministry of Railways

Director General, ISI ( *Ex-officio Member* )

*Secretary*

C. R. RAMA RAO

Deputy Director ( Civ Engg ), ISI

# BUREAU OF INDIAN STANDARDS

## Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha  
( Common to all Offices )

## Regional Offices:

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	{ 331 01 31 331 13 75 36 24 99
*Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola, CALCUTTA 700054	
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	{ 2 18 43 3 16 41 41 24 42
Southern : C. I. T. Campus, MADRAS 600113	{ 41 25 19 41 29 16
†Western : Manakalaya, E9 MIDC, Marol, Andheri ( East ), BOMBAY 400093	6 32 92 95

## Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	{ 2 63 48 2 63 49
‡Peenya Industrial Area 1st Stage, Bangalore Tumkur Road BANGALORE 560058	{ 38 49 55 38 49 56
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	5 36 27
53/5, Ward No. 29, R.G. Barua Road, 5th Byelane, GUWAHATI 781003	3 31 77
5-8-56C L. N. Gupta Marg ( Nampally Station Road ), HYDERABAD 500001	23 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	{ 6 34 71 6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005	{ 21 68 76 21 82 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
T.C. No. 14/1421. University P.O., Palayam TRIVANDRUM 695035	{ 6 21 04 6 21 17

## Inspection Offices ( With Sale Point ):

Pushpanjali, First Floor, 205-A West High Court Road, Shankar Nagar Square, NAGPUR 440010	2 51 71
Institution of Engineers ( India ) Building, 1332 Shivaji Nagar, PUNE 411005	5 24 35

\*Sales Office in Calcutta is at 5 Chowringhee Approach, P. O. Princep Street, Calcutta 700072

†Sales Office in Bombay is at Novelty Chambers, Grant Road, 89 65 28 Bombay 400007

‡Sales Office in Bangalore is at Unity Building, Narasimharaja Square, 22 36 71 Bangalore 560002